



# A-660

## ONE COMPONENT EPOXY ADHESIVE

### DESCRIPTION :

A-660 is a epoxy modified, room temperature cured, general purpose adhesive for bonding metal, ceramic, rubber, and most plastics. They are chemically resistant to many acids and bases as well as heat, water and oils.

### SPECIFICATION

Color	:	Light amber
Viscosity	:	@ 25°C 10,000 Cps
Specific gravity	:	@ 25°C 1.06
Solid content	:	60%
Solvent	:	Toluene
PH Value	:	6.8~7.5
Open time	:	@ 25°C 25 Min
Seting time	:	@ 25°C 4 Hr
Temperature rating	:	130°C
Flammability	:	UL.94 self-extinguishing
Tensile lap shear strength	:	70 Kg/cm <sup>2</sup>
Shelf life	:	6 Month
Package	:	1 kg, 15kg

傑地有限公司

UL MIL 絕緣材料·粘膠·溫控器材

台北 TEL:886-2-26008672 台中 TEL:886-4-25685848  
東莞 TEL:86-769-88188707 上海代理 TEL:86-21-58356975  
Home Page: [www.jasdi.com.tw](http://www.jasdi.com.tw)  
E-mail: [jasdikao@ms21.hinet.net](mailto:jasdikao@ms21.hinet.net)